



ECKO-Flex Duct
Reinforced, Non-collapsible
Flame Retardant



Order #: FDT-21624046BR - 8" x 4.6m, belt by ring, non-conductive duct
 FDT-30534005BB - 12" x 5m, belt by belt, non-conductive duct
 FDT1615BB - 16" x 15', belt by belt, non-conductive duct
 FDT-21624676BR - 8" x 7.6m, belt by ring, non-conductive duct
 FDT-30534010BB - 12" x 10m, belt by belt, non-conductive duct
 FDT1625BB - 16" x 25', belt by belt, non-conductive duct

Application: Recommended for industrial air ducting applications.

Product Features:



- Light Weight
- Good Crush Resistance
- Duct retracts to support storage in a duct bag or duct canister
- Wear Strip provide abrasion resistance
- Flame Retardant Materials

Construction Materials: 2-Ply PVC vinyl coated polyester fabric with integrated spring steel helix wire. Wear strip placed over the spring steel helix wire protects duct from scrapes and tears.

Temperature: -20°F to 180°F

Size: 8" x 4.6m 12" x 5m 16" x 15'
 8" x 7.6m 12" x 10m 16" x 25'

Color: Yellow with black wear strips

Duct End Terminations: Cuffs with belts, hose clamps, or nylon rings, as specified by customer.

